



# PRODUCT DATA SHEET

## KZN SAE 15W-40 (CH-4/SL)

### MULTIPURPOSE DIESEL AND GASOLINE ENGINE OIL

#### Description

KZN SAE 15W-40 is blended with refined high quality base oils including multifunctional additives which are suitable for universal performances over a long period.

#### Advantages

- High Temperature Stability
- Withstands very severe service conditions like four strokes and turbo charge.
- Reduce Oil consumption
- Longer drain intervals
- Reduce cylinder wear and keep pistons cleaner.

#### Applications

KZN SAE 15W/40 is recommended for turbo diesel and mixed fleet of both the diesel and petrol engines in severe loading services. Mixed fleet both old and new machines or equipment and stop start vehicles. In all types of generator sets and mobile hydraulic systems. The advanced detergent and load carrying additives used are capable of keeping engines super clean, protect stressed component, and control bore polishing.

#### Quality Levels

The SAE 15W-40 Multigrade Oil meets the following requirements:

API CH-4/ CG-4/CF-4/SJ/SL.

ACEA E7-04.

MB 228.2/3

MAN M3275

Volvo VDS-2

Cummins CES 20076/77/78(Pending).

MACK EO-M.

MTU/DDC Type 2.

#### Typical Characteristics

<b>SAE Viscosity Grade</b>	15W/40
<b>Viscosity @ 40C</b>	115.0cSt
<b>Viscosity @ 100C</b>	14.40cSt
<b>Kinematic Viscosity Index</b>	127
<b>Density @ 20C</b>	0.8860kg/l
<b>Pour Point</b>	-30deg.C
<b>Flash Point</b>	>200
<b>Appearance</b>	Bright and Clear