



PRODUCT DATA SHEET

KZN SUPER TWO STROKE OIL

LOW SMOKE SUPER MOTORCYCLE ENGINE OIL

Description

Super Two Stroke Oil is blended with refined high quality base oils including multifunctional additives ,ie antioxidants,anti-wear and anti-rust agents,detergents, dispersants to prevent pre-ignition and spark plug fouling.

Advantages

High miscibility /fluidity
Easily identified with its blue colour
Trouble free operations which prevents spark plug fouling and pre-ignition

Applications

Recommended for use in motorcycle engines as well as two stroke chainsaws and brush cutters.Low smoke product with excellent rust protection.Used for oil injection systems that disperses very quickly when added to fuel which enables the pre-mixtures to remain stable.
Manufacturer's recommendations should be followed to ensure correct ratioof oil/fuel mixture ie 1:20

Quality Levels

SUPER TWO STROKE OIL meets or exceeds the following performance requirements:

JASO FB levels and API TC levels

Typical Characteristics

Viscosity @ 100C	10.24 cSt
Viscosity Index	106
Density @ 20C	0.8700kg/L
Pour Point	-21 deg.C
Base Number	2.6 typ
Colour	Blue
Appearance	Bright and Clear
Water Crackle	Negative